





Auto Lab



FP-21T Precision

High Cost Performance Series



Lab Series

Most popular

Low cost, popular and X,Y,Z triple-axes control



- Spindle Speed: 41,000rpm
- Single Step Tool Change
- Standard Equipped Camera Monitoring System
- Cabinet (option)

Working area 229x320mm

Easy Operation! Single Step Tool Change



Tool change can be done without any complicated action such as thread fastening.

14511(0)(0)

• Spindle Speed : 60,000rpm

NEW

Single Step Tool Change

GYGAN

- Standard Equipped Camera Monitoring System
- Cabinet (option)



Standard Equipped 3-point pressure foot



Auto Tool Change Model



- Spindle speed 62,000 rpm
- 10 Auto Tool Change
- Standard Equipped

MITS

Camera Monitoring System • Cabinet (option)



MITS

• Spindle speed 100,000 rpm

Wide Working Area Model

ANDL-DW

- Spindle speed 62,000rpm
- 10 Auto Tool Change (20 by option)
- Standard Equipped Camera Monitoring System



400x365mm



Working area

229x300mm

Our PCB prototyping systems enable easy & high precision board making

- Ideal for in-house prototyping
- Time saving of product development
- Produces boards with the precision expected in a laboratory
- Processing without chemicals

FP-21T Series

High Precision Performance Series

FP-21T Most popular

Desktop type with 3-axes control system 3 models which have different Spindle speed: 40/U, 60, and 100.Air-floatation and noncontact pressure foot for 21THP.Ideal system for High-Frequency Circuit, Teflon Board, Flexible Films.



model 40/U

- Standard Equipped Camera Monitoring System
 Cabinet (option)
- Working area 350x250 mm

Ouble-sided boardAuminumOutputDouble-sided boardAuminumAcrylicImage: Characters on a panelImage: Characters on a panelImage: Characters on a panel

Capable of processing various materials besides substrate boards.

With your unique ideas, applications for FP-21T/21THP are limitless.

Hardware parts, panel engraving, supplementary work on finished board, and other works done with MITS prototyping machine are shown below.



Speaker cover



Puzzle pieces

50µm(2mil) line and space, the state of the art !

FP-21T Precision

- High performance spindle motor
- Standard Equipped Camera Monitoring System
- Cabinet (option)

Stepping method (three dimensional regulation) and non-contacting pressure foot (HP type) lead to the fine processing technology

This model features construction for high-rigidity and low center of gravity as well as a spindle motor with minimum level of runout, to ensure very low vibration making it ideal for the finest level of processing.

With our innovative Z-axis control (stepping method), the FP-21T Precision takes the advantages of the fine and fragile tools, and is capable of processing 50 m(2 mil) lines and spacing for the first time in the world as a desktop PCB prototyping machine. In comparison to the laser machine, FP-21T Precision is far superior in sharp cutting edge and cost performance.



(3)

Providing very beautiful fine and accuracy cutting finish on the prototype PCB is most required point for the PCB Prototyping Machine.



For in-house printed circuit board prototyping

Wide range of product line-up

In order to meet the increasing demand for miniaturization and high-density of PCBs in many fields of electronics, MITS is offering wide range of PCB prototyping machines including FP-21T Precision, the world first 50 μ m (2 mil) line/spacing milling machine, and many other machines for various purposes.

Made-in-Japan machines, renowned for quality and reliability

MITS has been enjoying high reputation as the leading Japanese manufacturer of PCB prototyping machines, offering the enduring, high-rigidity, and extraordinarily precise machines for many years.

All the manufacturing process of MITS machines is taking place in Japan, from design to construction. Thorough performance testing (by our own technical staff) ensures MITS prototyping systems to achieve fine-pattern processing.

Seamless integration from CAD designing to board making

You can produce your boards by importing your CAD data (Gerber or DXF output format) to our software enabling smooth process from CAD designing to board making. Moreover, together with MITS original software suites and options, you will have even more useful and enhanced integrated MITS PCB prototyping systems.

You can produce single, double sided, multilayer, and high-density boards rapidly !



For various types of the boards

MITS PCB prototyping machine can mill various types of the boards from normal circuit boards to extremely thin circuit boards. Besides PCBs, MITS PCB prototyping machine achieve the fine processing on the surface of other materials such as aluminum or acrylic.





An example of milling lines on a silicon wafer

Options enable you to process even more precisely

Fiducial positioning camera (Standard equipment) Board surface can be displayed 30,60 times magnified

Simply by equipping the color microscope with the machine and by connecting to the PC via USB, you can display the surface of the substrate board with 30,60 times magnification. Marking indicator and measurement function make it possible to align with high-precision and to measure the width of track/pattern.







Precise model VTP-CRM Precise vacuum table made of the ceramics. Suitable for the material whose thickness is as thin as 50µm (2 mil).



Standard model VT-ABS Vacuum table made of the plastic resin. Suitable for the material thicker than 200µm (8 mil).

Specification	VTP-CRM	VTP-ABS	VT-ABS
Working area WxD (mm)	150 x 120 (5.9"x 4.7")	300 x 170 (11.8"x 6.7")	280x215 (11.0"x 8.5")
The minimum thickness	50µm (2mil)	200µm (8 mil)	200µm (8 mil)
Porous surface material	Ceramics	Plastic resin	Plastic resin
Applicable model	FP-21T Precision	FP-21T	Lab series

Surface detecting Device (option)



Surface detecting device measures the thickness of the PCB.



As the head presses the board without direct contact by air floating, it leaves no undesirable traces on the board surface. Suitable for milling thin substrate boards and soft substrate boards such as teflon circuit boards.



* Required for air compressor

Tool protrusion equipment (option)

You can measure the protrusion length of the tool from the pressure foot by the micro meter.



Easily viewable gauge



Fine tuning

Minimum measuring quantity : 0.001mm (0.04 mil) Maximum measuring quantity 0.140mm (5.5 mil) Dimension W x D x H (mm) : 115 x 58 x 25 (4.1" x 2.3" x 1.0")

OK

Specifications		NEW	Auto-tool- change	Auto-tool- change	
Model	Eleven Lab	Eleven Lab 60	Auto Lab	Auto Lab 10	0
Working area (X/Y/Z) (mm)	229x320x10*6 (30*5) (9.0"x12.6"x0.4")	229x320x10 *6 (9.0"x12.6"x0.4")	229 x 300 x 45 * 6 (9.0"x11.8"x1.8")		
Table size (mm)	296x396 (11.6"x15.6")		296x370 (11.6"x14.5")		
Minimum width Line & Space (mm)	0.1 (4mil)				
Control axis	X , Y , Z				
Control motor	Stepper Motor				
Resolution (µm) *1	0.625 (0.	0.625 (0.0246 mil) 0.156 (0.00614 mil)		00614 mil)	
Maximum Travel speed *2	55 (2.17")				
Spindle speed (min ⁻¹) // motor	5,000 - 41,000 DC Spindle	5,000 - 60,000 DC Spindle	5,000 - 62,000 DC brushless Spindle	5,000 - 100,000 HF Spindle	*4
Drilling (mm)	0.2 - 3.175 (8-125mil)				
Maximum drilling cycles * 3	55				
Tool Change	Manual Single Step Tool Change		Automatic / 10		
Pressure foot (Board Press Method)	One point of foot (3point:option)	3 point of foot	3 point	of foot	
Camera System	Standard 30x				
Power consumption (VA)	150		200		
Machine dimensions WxDxH (mm)	435x575x430 (17.2"x23"x17")				
Machine weight (kg)	Approx.28 (62 lbs)		Approx.34 (76 lbs)		
Features	Low-priced Popular model		Auto-tool-change	Ange High speed spindle motor Auto-tool-change	
	*1 The minimum traveling figure	s for ordering each 3 axis movem	ent. *2 Optimum speed for cut	ting depends on tool,	

* 1 The minimum traveling figures for ordering each 3 axis movement. They do not represent the accuracy of axis positioning.

Tools and peripheral equipments







- Dimensions WxDxH (mm) 500x580x450
- Weight 10kg

Applicable model: Eleven Lab, Auto Lab, Auto Lab 100

Types of Tools

material of board and so on.

- Milling bit
- (60°or 90°)
- Diamond milling bit (30 times more durable)
- HF milling bit
- 0.05mm 0.5mm (2 20mil) • Rubout bit
- Drilling bit
- 0.05 3.175mm (2 125mil) • Routing bit
- 1.0, 1.5mm (39, 59 mil)
- Aluminum engraving cutter 0.8, 1.0, 2.0mm



Auto-tool- change			Specifications	
Auto Lab W	FP-21 T	FP-21T Precision	Model	
400x365x45 *6 (15.7"x14.3"x1.8")	350x250x25 *7 (14"x10"x1")	150x150x25 *7 (6"x6"x1")	Working area (X/Y/Z)(mm)	
490x490 (19.3"x19.3")	460x450 (18"x18")	240x380 (9"x15")	Table size (mm)	
0.1 (4	4mil)	0.05 (50µm) (2mil)	Minimum width Line & Space	
	Χ,Υ,Ζ		Control axis	
Stepper Motor	5 phase Stepper Motor	5 phase Stepper Motor	Control motor	
0.156 (0.00614 mil)	4 (0.16 mil)	1 (0.04 mil)	Resolution (µm) *1	
80 (3	80 (3.15") 60 (2.4")			
5,000 - 62,000 (model 60) 5,000 - 100,000 (model 100) *4	5,000 - 40,000 (model 40/U) 5,000 - 60,000 (model 60) 5,000 - 100,000 (model 100) * 4	5,000 - 40,000 Dynamic runout∶less than 10µm DC Spindle	Spindle speed (min ⁻¹) // motor	
0.2 - 3.175 (8-125mil) 0.05 - 3.175 (8-125mil)			Drilling (mm)	
55	8	Maximum drilling cycles (drill/min.) * 3		
Automatic / 10 20 tools by option	Man Single Step T	Tool Change		
3point of foot	3point of foot (Non contact:option) *4	Air *4	Pressure foot (Board Press Method)	
Standard 30x Standard 60x			Camera System	
200	25	Power consumption (VA)		
635x643x430 (25"x25.3"x17")	620x505x420 (24"x20"x17")	415x500x375 (16"x20"x15") 125x235x305 (5"x9"x12")	Machine dimensions WxDxH (mm)	
Approx.41 (90 lbs)	Approx.42 (93 lbs)	Machine: 36 (80 lbs) Controller: 4 (9 lbs)	Machine weight (kg)	
Wide area type Auto-tool-change	High precision, High rigidity Various material milling	High precision 50µm milling, High rigidity	Features	
*3 This is a repeat count of drill's up on the maximum stroke. Optimum strokes depends on the	and down *4 Air compressor required *5 without aspiration nozzl diameter of tool.	e *6 z-axis stroke 50mm The ab a	ove machines have CE	

• Precision ring-setter (manual)

Features

- You can attach or detach the ring to the tools.
- Standardize the depth of the tools for the auto tool change machine.
- Effective in adjusting to the material of varied thickness.
- Applicable for tools less than 0.1mm.



Jetstream

Super Cleaner "Jetstream" creates pollutionfree quiet factory environment

- Collects 99.97% of milling particle debris as fine as 0.3microns, while 90% for average household vacuum cleaner. (MITS inhouse experiment data)
- Jetstream noise level is 57dB, while 70dB for average household vacuum cleaner.
- Linked with the milling machine and power supply is automatically turned on and off.
- Maximum suction pressure is 22,500pascals and the pressure level can be freely and automatically adjusted.
- Compact and lightweight.
 255Wx360Dx310H mm, 12.5kg
- Power consumption 630VA.

Available spare parts • Filter Bag (1 pack with 5 pieces) • HEPA Filter

(1 pack with 1 piece) • Exchangeable Motor Brush (1pack with 2 pieces)



Software

Design Pro Chart



Design Pro (Standard Accessory)

Design Pro contains Converter and CAD application. The function of Converter is editing PCB pattern data, and data import/export.

And, CAM application is designed to control our PCB prototyping machines.

(For drawing and editing PCB patterns, our software EASY CAD is available as an optional extra.)

Converter

This application has functions to import Gerber Data (RS274D, RS274X), or DXF data, and automatically generate PCB milling data based on imported PCB pattern data.

• CAM

This application is designed to control and set up MITS PCB prototyping machines.

The machine runs along the generated PCB milling data on Converter or Easy CAD, also manual operation command.

Any required setup to run machine is set in this application.

• System Requirements

OS: Windows 10/8/7/Vista/XP (SP2)

EASY CAD option

- By using this easy-to-operate software, you can easily draw the patterns exactly as you want.
- Straight forward and Easy to use.
- Popular for high-frequency patterns.

Functions & Features

- Pattern Creation After setting the line
- After setting the line width, land/pad width and hole diameter, create a pattern on screen.

Pattern Drawing

Diagrams of points, straight lines, arcs and characters can be produced.

- You can draw patterns by inputting numerical values.
- Editing Function

Editing functions such as line extension, line cutting, beveling (rounded corner or 45° bevel), object repositioning, copying, deleting, offsetting and hatching are possible.

CAD Softwares of Other Companies

Convertible file format

Compliant Softwares

- Gerber
- GerberX (274X)
- Excellon Drill output data
- DXF

- CR-5000 (ZUKEN)
- Protel (Altium Designer)
- PADS
- OrCAD
- Win PCB
- Eagle
- Microwave Office
- Auto CAD (Auto Desk)
- CADLUS
- Ansoft DesignerHFSS
- PCBE AltiumDesign Spark
- Other

1511

MITS Electronics

http://www.mitspcb.com/ E-mail:staff@mits.co.jp 1-2-21, Kajino-cho Koganei-Shi, Tokyo,184-0002 Japan

